

FARMER II

Use:

Light fitting for the illumination of indoor and outdoor industrial spaces.



CE		IP54	Ta -25°C ÷ +40°C
VVG 	EVG 	Carton (mm/pcs): 1000 x 280 x 280 / 1 650 x 280 x 280 / 1 860 x 440 x 280 / 2	
E27	230V 50Hz		

Technical description:

The body is made of steel sheet and finished with powder paint. The inorganic glass cover with a seal and a protective basket is fixed to the body with four metal caps. According to the individual types, the light fitting includes: an AISi terminal box, a steel pipe finished with powder paint or a galvanized steel sheet boom. The light fitting is made as a through light fitting and is provided with two cable outlets. The max. cross-section of the connecting conductors is 4 mm².

Installation:

On the ceiling, wall.

Versions:

Optional version of light fittings with reinforced corrosion protection – version "pz", version with a protective steel basket – version "K", version with a protective polycarbonate basket and stainless steel caps – version "p", version with an electronic ballast (EVG) - version "EP".

To order:

Protective steel basket 1-99.6248, PMMA protective basket 182.5005, protective polycarbonate basket 182.2540, glass cover 232.5068/1, metal cap 4-99.8470/01, stainless steel cap 4-99.6180/01.

Type	Recommended light source [W]	Part of light fitting	Weight [kg]
541 17 01	High-pressure mercury discharge lamp 125	terminal box	7.1
541 24 01	High-pressure sodium discharge lamp 70	terminal box	7.3
541 24 01	High-pressure halide lamp 70	terminal box	7.3
541 24 01 EP	High-pressure halide lamp 70	terminal box	7
542 02 01	High-pressure mercury discharge lamp 125	pipe and terminal box	7.1
542 07 01	High-pressure sodium discharge lamp 70	pipe and terminal box	7.3
542 07 01	High-pressure halide lamp 70	pipe and terminal box	7.3
543 01 01	High-pressure mercury discharge lamp 125	boom	7.1
543 05 01	High-pressure sodium discharge lamp 70	boom	7.3

*By adding the letter "K" after the type designation, the light fittings will be provided with protective baskets (541 17 01 K)

**By adding the letter "p" after the type designation, the light fittings will be made with protective polycarbonate baskets and stainless steel caps - for harsh conditions (541 17 01 p)

**By adding the letters "pz" behind the type designation, the light fittings will be made with reinforced corrosion protection - for extra harsh conditions (541 17 01 pz)

Any combinations of special versions at the customer's request.