

FARMER III

Use:

Light fitting for the illumination of indoor and outdoor industrial spaces. The light fitting is uncompensated.



CE		230V 50Hz	IP54	Ta -25°C ÷ +55°C (t) -40°C ÷ +40°C (F)
VVG 	E27	Carton (mm/pcs): 650 x 280 x 290		

Technical description:

The light fitting consists of a ballast box – an AlSi alloy casting and a body made of steel sheet, finished with powder paint. The inorganic glass cover with a seal and protective polycarbonate basket is fixed to the body with four stainless steel caps. The max. cross-section of connecting conductors is 4 mm².

Installation:

On the ceiling, with a suspension eye ø30 mm.

Versions:

Version with a protective steel basket – version "K".

To order:

Protective steel basket 1-99.6248, protective polycarbonate basket 182.2540, glass cover 232.5068/1, stainless steel cap 4-99.6180/01.

Type	Recommended light source [W]	Weight [kg]
541 18 01 t	High-pressure mercury discharge lamp HQL 125	7.1
541 18 02 t	High-pressure sodium/halide discharge lamp 70	7.1
541 18 03 F	Halogen lamp HCI-E 150	7.5
541 18 04 F	Halogen lamp HQI-E 100	7.5

By adding the letter "K" after the type designation, the light fittings will be provided with protective baskets (541 18 01 Kt)

