

HEADLIGHT

Use:

Light fitting for the illumination of billboards, shop windows, architectural units, ancient monuments, building facades, subways, construction sites, car parks.



| | | | | |
|--------|--------------|--|------|---------------------|
| CE | 230V 50Hz | | IP65 | Ta -25°C ÷ +30°C |
| WG | E27 | Carton(mm/pcs): 310 x 200 x 150 / 1 | | |

Technical description:

The light fitting body is made of AlSi alloy and finished with powder paint. There is an M20x1.5 outlet for a power cable on the side of the light fitting. The base plate with electrical equipment is fixed inside the light fitting. The light fitting reflector is asymmetrical, made of anodized aluminium. The cover with protective hardened glass is fixed to the body. The steel holder allows turning the floodlight to the required position. The max. cross-section of the connecting conductors is 2.5 mm².

Installation:

On the ceiling, wall or another solid substrate (structure) ensuring firm connection.

To order:

Protective glass cover.

| Type | Recommended light source [W] | Socket | Weight [kg] |
|-----------|--|--------|-------------|
| 743 05 12 | High-pressure mercury discharge lamp 125 | E27 | 3.5 |
| 743 05 70 | High-pressure sodium discharge lamp 70 | E27 | 4 |
| 743 05 70 | High-pressure halide lamp 70 | E27 | 4 |

