


KOULE A



Use:

Light fitting for the decorative light fitting of pedestrian zones, parks, orchards and other public areas.

CE	230V 50Hz		VVG 	IP54/23
E27	EVG DIMM 	Ta -25°C ÷ +30°C		
Carton (mm/pcs): 550 x 550 x 510 / 1				



Technical description:

The light fitting consists of a carrier and body (AlSi castings) connected with screws and two semi-spherical covers. A prepreg decorative strip is fixed to the body from the outside and electrical equipment from the inside. The top cover is firmly screwed to the body, the bottom cover is fixed with PC caps. The light fitting is made in green (Z) or grey (S) colour. The light fitting is to be fixed to a column shank $\varnothing 60$ mm. The max. cross-section of the connecting conductors is 2.5 mm².

Installation:

On a column.

Versions:

The light fittings are made in a version with an electromagnetic ballast (VVG), for high-pressure sodium or halide discharge lamps. The light fittings can also be equipped with electronic adjustable ballasts (EVG DIMM). Type 446 16 xx – both covers made of opal PMMA, the luminous flux is non-directional. Type 446 17 xx – the top cover is made of prepreg, the bottom cover of clear PMMA, luminous flux is directed by a symmetrical reflector.

To order:

Bottom cover (clear type 042.5549/1, opal type 042.5550/1), PC cap 317.5016/1.

Type	Recommended light source [W]	Electronic ballast dimmable	Weight [kg]
446 16 01	High-pressure sodium discharge lamp 50	-	8
446 16 02	High-pressure sodium/halide discharge lamp 70	-	9
446 17 01	High-pressure sodium discharge lamp 50	-	8
446 17 02	High-pressure sodium/halide discharge lamp 70	-	9