


## Use:

Light fitting for the illumination of pedestrian zones, parks, orchards and other public areas.



CE	230V 50Hz		VVG 	EVG DIMM 
E27	E40	IP54	Ta -25°C ÷ +30°C	
Carton (mm/pcs): 705 x 705 x 550 / 1				



## Technical description:

The top cover of the light fitting is made of prepreg, the bottom cover is made of opal PMMA. The nut for fixing the top cover is made of silamide. The pedestal is made up of a prepreg cone and an AlSi alloy holder for fixing onto a column. The removal base plate with electrical equipment is fixed to the light fitting pedestal. The light fitting is to be fixed to a column shank  $\varnothing 60$  mm. The max. cross-section of the connecting conductors is 2.5 mm<sup>2</sup>.

## Installation:

On a column.

## Versions:

Light fittings are made in versions with an electromagnetic ballast (VVG), for high-pressure sodium, halide or mercury discharge lamps. Light fittings can be also equipped with electronic adjustable ballasts (EVG DIMM).

## To order:

Bottom cover 342.2554, silamide nut 412.2560.

Type	Recommended light source [W]	Electronic ballast dimmable	Weight [kg]
446 27 05	High-pressure sodium discharge lamp 50	-	13
446 27 53	High-pressure sodium discharge lamp 50	Yes	13
446 27 07	High-pressure sodium/halide discharge lamp 70	-	13
446 27 73	High-pressure sodium discharge lamp 70	Yes	13
446 27 09	High-pressure sodium/halide discharge lamp 100	-	13
446 27 01	High-pressure mercury discharge lamp 80	-	13
446 27 03	High-pressure mercury discharge lamp 125	-	13