



OPAL

Use:

Light fitting for the illumination of pedestrian zones, parks, orchards and other public areas.

CE	230V 50Hz		VVG 	IP65
E27	E40	Ta -25°C ÷ +30°C		
Carton (mm/pcs): 550 x 550 x 550 / 1				



Technical description:

The light fitting body is a PC moulding. The optical cover is made up of an opal PMMA moulding $\varnothing 450$ mm. The removal base plate with electrical equipment is fixed to the light fitting body by a three-point bayonet. The light fitting is to be fixed to a column shank $\varnothing 60$ mm. The max. cross-section of the connecting conductors is 2.5 mm².

To order:

Stainless steel grille, opal cover, prismatic, clear or with top silver paint.

Type	Recommended light source [W]	Electronic ballast dimmable	Weight [kg]
446 36 50	High-pressure sodium discharge lamp 50	-	3.8
446 36 70	High-pressure sodium/halide discharge lamp 70	-	4.1
446 36 73	High-pressure sodium discharge lamp 70	Yes	3.5
446 36 10	High-pressure sodium/halide discharge lamp 100	-	4.3
446 36 80	High-pressure mercury discharge lamp 80	-	3.6
446 36 12	High-pressure mercury discharge lamp 125	-	3.8

