

SPOTLIGHT

Use:

Light fitting for the illumination of billboards, shop windows, architectonic units, ancient monuments, building facades, subways, construction sites and car parks.



CE	230V 50Hz		IP65	Ta -25°C ÷ +30°C
WG 	 Rx7S	R7s	RX7s-24	
Carton (mm/pcs): 380 x 200 x 200 / 1				

Technical description:

The light fitting body is made of AlSi alloy and finished with powder paint. There is a PG 13.5x1.5 outlet for power cable at the rear of the light fitting. The base plate with electrical equipment is fixed inside the light fitting. The light fitting reflector is symmetrical, made of anodized aluminium. The cover with protective hardened glass is screwed into the body. The steel holder allows turning the floodlight to the required position. The max. cross-section of the connecting conductors is 2.5 mm².

Installation:

On the ceiling, wall or another solid substrate (structure) ensuring firm connection.

To order:

Protective glass cover.

Type	Recommended light source [W]	Socket	Weight [kg]
723 06 01	Halogen linear bulb 150, 200, 300, 500 Halogen linear bulb ENERGY SAVER 120, 160, 230, 400	R7s	2.8
743 06 70	High-pressure sodium discharge lamp NAV-TS 70 High-pressure halide lamp HQI-TS 70	RX7s	4.3
743 06 15	High-pressure sodium discharge lamp NAV-TS 150 High-pressure halide lamp HQI-TS 150	RX7s-24	5

