

# TURTLE

## Use:

Light fitting for the illumination of indoor and outdoor industrial spaces.



CE		230V 50Hz	IP66	E27
	<b>Ta</b> -25°C ÷ +40°C -50°C ÷ +80°C version "Ht"			
<b>Carton (mm/pcs):</b> 400 x 400 x 190 / 1				

## Technical description:

The light fitting body and flange are AlSi alloy castings finished with powder paint. The optical cover is made of hardened glass. There are two cable outlets on the light fitting sides. Electrical equipment is installed inside the light fitting. The light fitting is designed as a through light fitting. When the light fitting is used as a terminal light fitting, the free cable outlet is blinded with a plug. The max. cross-section of the connecting conductors is 4 mm<sup>2</sup>.

## Installation:

On the ceiling, wall or another solid substrate (structure) ensuring firm connection.

## To order:

Ballast box BOX 2 for mounting of the discharge lamp, blinding plug PG11/M16, glass cover 232.5070, protective basket 1-99.8534/1.

Type	Recommended light source [W]	Voltage [V/Hz]	Weight [kg]
511 33 02	2 x Halogen bulb Philips EcoClassic 105	230 / 50	6
511 33 02	2 x Bulb CLAS 200	230 / 50	6
511 33 02	1 x Blended lamp HWL 160	230 / 50	6
511 33 02	1 x High-pressure mercury discharge lamp HQL 80	230 / 50	6
511 33 02	1 x High-pressure mercury discharge lamp HQL 125	230 / 50	6
511 33 02	2 x Compact fluorescent tube DULUX EL 23	230 / 50	6
511 33 02 Ht	2 x Halogen bulb Philips EcoClassic 70	24 V DC	6
511 33 02 Ht	2 x Bulb CLAS 100	230 / 50	6

