


TAURUSLED



Use: Light fitting for the illumination of heavy indoor and outdoor industrial spaces with a high level of mechanical stress.

Technical description:

The light fitting body and flange are AISi alloy castings finished with powder paint RAL 5012. The optical cover is made of tempered glass. A steel suspension with eyes is fixed to the top part of the body. There are two cable outlets on the light fitting sides. There is an LED module built inside the light fitting and it is comprised of a board fitted with LEDs and a power supply. The light fitting is designed as a through light fitting, for three-phase connection (five-core cable). When the light fitting is used as a terminal light fitting, the free cable outlet is blinded with a plug. The max. cross-section of the connecting conductors is 4 mm².

Control: DALI-2 (TRIDONIC)

Installation: With a steel suspension with eyes $\varnothing 16$ mm.

Versions:

The light fittings are made in a version with an electronic adjustable ballast (EVG DIMM). Light fittings are provided with a self-resetting thermal fuse and surge guard up to 10 kV. Standard light fittings are available with cable outlets M25x1.5, optionally with cable outlets M20x1.5.

To order:



Shade 154.5041/02



Holder for mounting on the ceiling 4-99.7995



Holder for mounting on the wall 338.2735



Spanner 3-99.6159

		IP66	198-264V AC 176-280V DC
			Ta -35°C ÷ +50°C
Carton (mm / ks) 410 x 240 x 240 / 1			

Type	Power input [W]	Luminous flux [lm]	Angle of beam [°]	Colour temperature [K]	CRI	Weight [kg]
591 46 01	100	14000	120	4000	>80	12,5
591 46 02	80	11000	120	4000	>80	12,5
591 46 03	65	9000	120	4000	>80	12,5